



About Our Products

Nite Time Decor has been designing and installing landscape lighting systems since 1998. Using our extensive experience, we have developed our own exclusive product line that delivers efficiency, performance, and value to our clients. As we've developed each product, we have focused primarily on construction, design, and value-as the product has to be durable, but also applicable and affordable. We are not interested in installing systems that do not perform long term-we want each installation to look as good years from now as it did the day it was installed.

Long-lasting Construction Stand Up to Harsh Climate **Balanced Value**

NTD Installation Accessories **NTD Transformers**

NTD Fixtures

The long-term value and performance of a landscape lighting system can be limited by using poor-quality fixtures. At Nite Time Decor, we recognize this, and have secured our own exclusive product line, ensuring that each job is done using the highest quality components. We've developed a fixture for every application—with most products being constructed of durable, cast

Beryllium Sockets 25' Lead 18 Gauge wire **Pre-Greased Sockets Heat Shrink Protected Wires Thumb Screw Adjustments**



SPOTWB

A landscape lighting installation is only as good as its weakest point. That's why Nite Time Decor uses only the finest in installation tools and accessories. Each component we use has been selected or developed based on our years of field experience-we know what it takes to assemble a high-performance landscape lighting system.



Surface Wall Mount



Commercial Brass Well Light Grate



Gutter Mount Bracket

The transformer serves as the 'heartbeat' of the landscape lighting system. Our transformers are designed for performance-constructed of the most durable materials with the most efficient operation. We carry transformers that are suited for today's LED projects as well as larger transformers designed for big installations. Transformers are available in 50 to 600 watt sizes.



75W Transformer



300W Transformer



600W Transformer

NTD Lamps

The Lamp does the lighting, thus it is critical to use the best quality product to achieve the optimum results. Our LED lamps use only CREE LED Chips. We stock PAR36, MR16 MR11, and Bi-pin LED retro lamps with wattage and beam spread options. Furthermore, we stock a complete selection of incandescent lamps in a variety of wattages and beam spreads to meet your application.





PAR36



MR16



MR11



NTD Controllers

Automation of your landscape lighting system creates convenience and cost savings for you-your system can be set to turn on and off whenever you want, and you don't have to worry about it. We carry a selection of the most technologically-advanced controllers in the industry, which can be incorporated into your landscape lighting system quickly and efficiently.



Dimmer Switch



PhotoCell Timer



Astro Timer

NTD Limited Time Warranty

Nite Time Decor guarantees the quality of our products and installation with one of the most comprehensive warranties in the industry. It protects the system and components for years and is effective after the original installation is completed. The warranty DOES NOT cover acts of nature, such as lightning strikes and damage due to physical abuse or vandalism. The warranty is void if anyone other than a Nite Time Decor contractor accesses the transformer for any reason other than the timer adjustment. We will make timely replacements and/or repairs as described below at no additional charge.

Lighting Control Automation Warranty

Nite Time Decor timers, controls, and other automation modules carry a 1-year limited warranty.

Lamp Warranty

Nite Time Decor lamps are covered by a 5-year limited warranty from the initial date of system installation. Only when a Nite Time Decor contractor replaces or installs the lamps does the warranty apply. The installation of the incorrect lamps by the property owner or another firm that causes system failure and/or fixture damage are not covered by warranty.

Transformer Warranty

Nite Time Decor outdoor transformers carry a lifetime warranty.

Light Fixture Warranty


Nite Time Decor guarantees light fixtures for a lifetime, from the installation date.

Wire Warranty

Nite Time Decor outdoor low-voltage wire is covered by a 10-year warranty.

Installation Warranty

Nite Time Decor guarantees installation for one (1) year from installation date. We offer a lifetime warranty on any lighting system that we design, install and maintain. If you choose not to maintain your lighting system with our current maintenance program, your system will be covered only to the limits listed above, or the limits of the individual manufacturer's warranty of the products used in the design. This warranty covers the performance of the fixtures, transformer and installation. All quality fixtures will experience some finish changes over time. This will not affect their performance, rather increases their appeal. All automation components are covered by their specific manufacturer's warranty.



Up-Lighting

This technique consists of lighting a property from the bottom up for an elegant effect



Down-Lighting

Consist of lighting features downwards from the top



Highlighting

This method is used to bring attention to certain elements like trees, walls, etc.



Moon Lighting

Used to simulate moon light by placing lamps above trees, walls, etc





RGB Lighting

Used to bring full color range and create unique moods and styles



Wall-Washing

Used for highlighting walls with varying flood patterns



Path Lighting

Used for lighting driveways, sidewalks, walkways to create paths of light



Accenting

This technique is used for lighting up stairs, or platforms for night enjoyment



Silhouetting

This technique is used for creating silhouttes of greenery like trees, bushes, etc.



Color Temperature (KELVINS) Kelvins is a measurement used to describe the color temperature of a light source. This is the specification commonly referred to as CCT Color Correlated Temperature. It's a gauge of how yellow or blue a white light source appears to the human eye. Landscape lighting scale is typically from 2500K up to 5700K that a description of the warmth or coolness of a light source. The landscape industry has landed on 2700K as standard Warm White, 300K as standard for Neutral White, and 5000K as Cool White.

WARM WHITE

At the lower end of the scale, from 2000K to 3000K, the light produced is called "warm white" and ranged from orange to yellow white in appearance.

NEUTRAL WHITE

Color temperatures between 3100K and 4500K are referred to as "neutral white" or "bright white" lamps within this range will emmit more neutral white light and may even have a slightly blue tint.

COOL WHITE

Above 4500K brings us daylight color temperature of light. Lamps with 4500K and above will give off blue-white light that mimics daylight.

CRI Color Rendering Index

Another part of color temperature is CRI Color Rendering Index. It is a measurement between 0 and 100. At zero (0), all colors look the same. A CRI of 100 shows the true color of an object. Incandescent is the standard all light CRI's are measured against. They are at 100. Typically a CRI of 80 to 90 are regarded as good and those with a CRI oof 90+ are excellent. General rule is the higher the CRI, the better the color rendering.



2700K CRI 100



2700K CRI 90



2700K CRI 70

Watts

Watts are a measurement of power consumption. With traditional incandescent lights typically the higher the wattage, the brighter the light. With LED lamps this is different because there is no hard fast rule to correlate wattage with output. One brand LED say 9W may emit enough Lumens to replace a 60W bulb, but another brand may need to use a less efficient LED, say 12W lamp to create enough lumens. In fact, that is why looking at Lumens versus Watts.

Lumens

Lumens is a measurement of total light output also known as the **brightness** of the bulb. More lumens means a brighter light, fewer lumens means a dimmer light.

Lumens are to light what:

Pounds are the bananas, Gallons are to milk

Lumens let you buy the amount of light you want.
When considering new bulbs, think lumens not watts.

100w Halogen is 1600 lumens, equal to a 10w LED bulb 50w Halogen is 800 lumens, equal to a 7w LED bulb 25w Halogen is 400 lumens, equal to a 5w LED bulb 20w Halogen is 320 lumens, equal to a 4w LED bulb 10w Halogen is 160 lumens, equal to a 2w LED bulb

All numbers are average due to various manufacturers.

Lightbulb **Shapes/Sizes**

Lamps are described in many ways. First by **Base** i.e. E26, E11, GU5.3, Shape i.e. A, C, G, **Size** i.e. 16, 19, 30, 36



Base


- 1. Candelabra E12 North America, E11 Europe
- 2. Intermediate E17 North America, E14 (ES, SES) Europe
- 3. Medium/Standard E26 (MES) North America, E27 (ES) Europe
- 4. Mogul E39 North America, E40 (Goliath ES) Europe
- 5. Bipin G4, 5.3 low voltage GU10 line voltage












Shape

Sizes

Typically described first by a letter, then a number to reflect the shape and size of lamp. The letter refers to the shape, and the number refers to size (more on that later).

- A. Arbitrary, Angle most resembles a standard bulb
- C. Conical, Candle often referred to Christmas light bulb
- **G.** Globe round or circular
- **S.** Sign called straight sided. Traditionally used in signs.
- ST. Straight tapered often seen in vintage-edison style lamps
- R/BR. Reflector typically make up flood type lamps
- MR. Multifaceted Reflector a directionally focused lamp
- PAR. Parabolic Aluminized Reflector like BR lights, but more directional





Solid Protection

- Not rated for protection
- Protection against solid objects larger than 50mm, but not against deliberate contact (contact with open hand palm)
- Protection against solid objects larger than 12mm (contact from finger)
- Protection against solid objects larger than 2.5mm (wire or tools)
- Protection against solid objects larger than 1mm (slender screws or nails, larger insects or potentially invasive small objects)
- Partial protection against dust and smaller particles
- Full protection against dust and other similar particles

IP Rating Example



Water Protection

- Not rated for protection
- Protection against vertical falling water droplets (condensation)
- Protection against vertical falling water droplets when tilted at 15 degrees
- Protection against moisture spray at up to 60 degree angles
- Protection against splashing water from any direction for a minimum of 10 minutes
- Protection against low-pressure jets of water
- Protection against powerful jets of water at a rate of 100 litres per minute (100kPa of pressure at a distance of 3m for 15 minutes
- Protection against full immersion up to 1m in depth for 30 minutes. Always check manufacture specifics for products with this rating
- Protection against full immersion up to 1m or more in depth for more than 30 minutes. Always check manufacture specifics for products with this rating.



In the gauges of wire, a gauge number describes the number of dies through which the wire has been pulled in order to reduce it down to a given diameter.

$For informational \ purposes \ the \ landscape \ wire \ chart \ is \ suggested \ wire \ size.$

Watts	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	200
Feet																				
40	16	16	16	16	16	16	16	16	16	14	14	12	12	12	12	12	12	12	12	12
60	16	16	16	16	16	16	16	16	14	14	14	12	12	12	12	12	12	12	12	10
80	16	16	16	16	16	16	14	14	14	14	14	12	12	12	12	10	10	10	10	10
100	16	16	16	16	14	14	14	14	14	12	12	12	10	10	10	10	10	10	10	8
120	12	12	12	12	12	12	12	12	12	12	10	10	10	10	10	8	8	8	8	8
142	12	12	12	12	12	12	12	12	10	10	10	10	10	8	8	8	8	8	8	8
160	12	12	12	12	12	12	12	10	10	10	10	8	8	8	8	8	8	8		
180	12	12	12	12	12	12	10	10	10	10	8	8	8	8	8	8				
200	12	12	12	12	12	12	10	10	10	8	8	8	8	8	8					
220	12	12	12	12	12	10	10	10	8	8	8	8	8							
240	12	12	12	12	10	10	10	8	8	8	8	8								
260	12	12	12	12	10	10	10	8	8	8	8									
280	12	12	12	10	10	10	8	8	8	8										
300	12	12	12	10	10	10	8	8	8	8										
320	12	12	10	10	10	8	8	8	8											
340	12	12	10	10	10	8	8	8	8											
360	12	10	10	10	8	8	8	8												

Lamps

Our lamps are offered in a variety of different styles, lumen output, beam angles, and wattage.



Bipin LED Lamp

Beam Angle	360	
Lumens	320-410	
Watts	2, 3, 4	
Color	WW, NW	
CRI	80+	
Voltage	9-15VAC	
Hours	25,000	
Warranty	3 Years	



MR11 LED Lamp
MR11LED2W120CW

Beam Angle	24, 60
Lumens	150-180
Watts	2, 5
Color	WW, NW
CRI	85+
Voltage	8-25VAC
Hours	50,000
Warranty	5 Years



MR16 LED Lamp
MR16LED5W60BL

Beam Angle	15, 30, 60, 120		
Lumens	330-710		
Watts	4, 5, 7		
Color	WW, NW, CW		
CRI	85+		
Voltage	9-15VAC		
Hours	50,000		
Warranty	5 Years		



PAR36 LED Lamp

Beam Angle	24, 60, 120		
Lumens	420-1050		
Watts	6, 10, 13		
Color	WW, NW, CW		
CRI	85+		
Voltage	12-24VAC		
Hours	50,000		
Warranty	5 Years		

Spotlights vs Floodlights

Spotlights feature a shorter beam spread with longer light reach. Generally, these are used for accenting features in smaller areas like trees, statues, flag poles, etc.



Narrow Spot

Accents specific features like trees and statues. The narrow angle help concentrate light to a specific area.

Typical 15°



Narrow Flood

Emits a medium wide beam, used by businesses and homeowners for facade lighting.

Typical 30°

Floodlights feature a wide beam spread with a short light reach. These are generally used where areas require ample lighting. Some examples include exterior house walls, driveways, parking areas, large patios etc.



Wide Flood

Dispersed beam that covers larger areas. Commonly used for facades, signs, and other landscape applications.

Typical 60°



Super Wide Flood

Used in areas that require the widest amount of light. Often found in commercial/residential facades, garages & parking lots. **Typical 120°**

Spot Light Fixtures

Designed to highlight landscape or architectural features like statues, bushes, and more. Using narrow beam patterns, spotlights focus on single objects creating unique lighting visuals.



Weathered Brass Spot Light (SPOT-WB)

MR16¹ Weathered Brass Spotlight, PVC Ground Stake with Brass Lock Ring



Mini Spot Light (MSPOT-WB)

Cast Brass MR11² Mini-Spot Light Sphere with Orbital Base, PVC Ground Stake with Brass Lock Ring



Weather Brass Spot With Adjustable Shroud (SPOT-GL)

Weathered Brass MR16¹ Spot with Adjustable Shroud PVC Ground Stake with Brass Lock Ring



Spun Brass Spot Light

(SPOT-SB)

MR16¹ Spun Brass Spot Light, PVC Ground Stake with Brass Lock ring



Cast Brass Tree Down Spot

(TRSPOT-CB)


MR16¹ Down Spot, Tree Mounting Bracket with Orbital Base



Cast Brass Bullet Spot

(SPOT-WBS)

Weathered Brass MR16¹ Spot with Ground Slotted Stake







Cast Brass Recessed Spot (RSPOT-CB)

MR16¹ Spot with ABS Sleeve, IP68



Recessed Spot
With Glare Guard (RSPOT-GL)

Recessed MR16¹ Spot Cast Brass with ABS sleeve




Recessed Brass Spot

With Clear Convex Lens (RSPOT-150, RSPOT-170, RSPOT-180, RSPOT-360)

Recessed MR16¹ Brass Spot with Convex Clear Lens and 25' Wire Lead





Inground LED Well Light (WELL-NG)
Black ABS PAR36 Well Light³

LED Gimball Ring

Flood Lights

Used for lighting up wider areas like walls, tree canopies and more. With their wider beam spread, floodlights are great fixtures to use for security lighting, wall washing, and more.w



Spun Brass Flood Light (PARD-SB) Spun Brass PAR36⁴ Above Ground Flood Light



Weathered Brass Flood Light (PARD-WB) Weathered Brass PAR364 Above Ground Flood Light



Cast Brass Wash Light

Cast Brass MR16¹ or Bi-Pin⁵ Wash Light PVC Ground Stake with Brass Lock Ring




Cast Brass Mini Wash Light

(MWASH-WB)

Cast Brass Mini MR16¹ or Bi-Pin⁵ Wash Light PVC Ground Stake with Brass Lock Ring







6" Brass Path/Area Hat (D6PTH-HAT)
Weathered Brass Bi-Pin⁵ Path Hat Variable Mounting Stems⁶ Available




6" Decorative Area Hat (D6AREA-HAT)
Weathered Brass Bi-Pin⁵ Path Hat Variable Mounting Stems⁶ Available




7" Path Light Hat(7PTH-HAT)
Weathered Brass Bi-Pin⁵ Path Hat
Variable Mounting Stems⁶ Available



8.5" Two-Tiered Area Light
Weathered Brass (8.5AREA-WB)
Die-Cast Path Light
18" Stem Included
(Bi-Pin Sold Separately)



12" Area Light Hat Weathered Brass (12AREA-HAT)(Bi-Pin Lamp & 12", 18", 24", 36"
Stems Sold Separately)



Path Light Stems (NTDSTEM12, NTDSTEM18, NTDSTEM 24, NTDSTEM36) Weathered Brass with Ground Stake Attached (Bi-Pin & Hats Sold Separately)

Post & Hanging Fixtures

Used for lighting patios, decks, or other smaller areas. Post lights mount on deck or posts, providing 360 lighting. Hanging lights mount on ceilings & provide downlighting for patios, decks, and other landscape areas.




Aged Brass Post Light WITH FROSTED LENS (POST-100)
Bi-Pin/MR16 Lamp (MR16 Lamp Sold Separately)



Aged Brass Hanging Light
ADJUSTABLE
(HL-100 *LEFT*, HL-200 *RIGHT*)
Hanging Light with 18" Chain
(MR16 Lamp Sold Separately,
HL-200 has twinkle cut outs)







Step Light 5" & 8" (STEP5/ STEP8)
Weathered Brass
(Bi-Pin Lamp Sold Separately)



3.48"

Cast Brass Eyelid (EYE-WB) Surface Mount Wall Sconce (Bi-Pin Lamp Sold Separately)





Lip Light(LIP-WB)
Weathered Brass Lip Light
(Bi-Pin Lamp Sold Separately)



















Tiki Torch Hat(TIKI-CB, TIKI-CB-STEM)
Weathered & Natural Brass
Also Functions as an Oil Lamp
(60" Stem & Bi-Pin Sold Separately)





4/6/9/12" Wall Sconce (scn-4, scn-6, scn-9, scn-12) Weathered Brass Dual Sockets on 6", 9", & 12" (Bi-Pin Lamp Sold Separately)





Cast Brass Water Light (UWLIGHT-CB, UWLIGHT-CB30) MR16 Underwater Light 30' Lead







60W & 75W 12V **Electronic Transformer** (60WLEDTRANS, 75WLEDTRANS)

60 & 75 Watt 12V **Electronic Tranformer**



Transformer (NTD-150WTRAN) Stainless Steel, Fully Potted, Insulated, Single Core, Inline Surge Protection



(NTD-300WTRAN) Stainless Steel, Fully Potted, Insulated, Single Core, Inline Surge Protection

300W 12V

Transformer



600W 12V **Transformer** (600WTRAN) 12V, 13V, 14V, and 15V,

Stainless Steel



Accessories



Gutter Mount Bracket

Gutter Mount bracket, Weathered Brass



Surface Mount

Weathered Brass Surface Mount - 2 hole Bracket -1/2in Thread



Tree Mounting Bracket

TREEM

Weathered Brass Mounting Bracket for NTD Tree Spot, includes mounting hardware



90 Degree Elbow

Weathered Brass 90 degree Elbow



Riser RISER6, RISER12, RISER24 RISER36

Weathered Brass Riser available in 6", 12", 24", 36"



Honeycomb Insert For MR16 Fixtures

MR16HONEYCOMB-R

Honey Comb Insert for MR16 Fixtures



Honeycomb Insert For PAR36 Fixtures

PAR36HONEYCOMB-R

Honey Comb Insert for PAR36 Fixtures



10/2, 12/2, 14/2 Direct Burial Cable, 250', 500'

12CABLE-250, 12CABLE-500 14CABLE-250, 14CABLE-500

Direct Burial Low Voltage Cable - 250ft or 500ft spool 10 year warranty



Quick Locking Wire Connector 100 PC

NTD-Q-LOC-100

NTD Quick locking Wire Connector, BAG-100



NTD Hub Box with Lid 10 per case

NTD logo wire connection Hub Box 10 per case



Spikecube Surge Protector 1 Outlet

Tripp Lite 1 Outlet Portable Direct Plug-in Surge Protector/ Suppressor 600 Joules



Grease Tube Connector Small PK/50

GTUBE-SM

Lithium grease filled tube for inground connections. Includes copper crimps. 50 per pack





The Decor Smart app gives you full control of your Decorsmart bulbs as well as your Permalites® 365 system. The app provides you with the ability to control your lights in many ways. Never worry about turning your system on or off when you use the app to set a timer for your lights. Set them to automatically turn on at sunset and turn off at sunrise.









EFFECTS

Select the perfect color pattern from a wide range of effects for events that bring your city together!

RGBW SLIDERS

Searching for a specific color to display? The RGBW sliders makes it simple to adjust to the perfect mood!

COLOR PICKER

Check out the built-in Color Picker to select from the millions of colors available!



Exterior Lighting Landscape Lighting

MR16 lamps have multiple uses not limited to illuminating exterior walls, around the pool, highlighting trees, sconces, and much more! They can be installed in our SPOT-WB or our other fixtures.





Perimeter Lighting



Using the RGB pebble light technology or RGB C9 bulbs to outline the roof you can light up any holiday.





Bring tranquility and depth to pool and spa environments. (Coming Soon)



Bistro Lighting **D**



Festive lighting for any occasion that can be hung on gazebos, patios, pergolas, or just about anywhere.

Interior Lighting



Remote Switch



Control lights from the wall or pull the remote out to keep it next to you.



Lamp Lighting A19 Globe Light



Great for table lamps, floor lamps, and more!





Strip Lighting



Strip lights can be mounted under cabinets, shelves, countertops, or other applications.



Flood Lighting



Indoor BR30. Great for ceiling lights. Outdoor BR30 is also available.







RGBW LED Flood Light Bulb INDOOR USE (DS-RGB-BR30IN-A)

BR30 Flood Light Bulb Bluetooth Compatible (Outdoor Bulb Sold Separately)





RGBW LED Flood Light Bulb OUTDOOR/INDOOR USE (DS-RGBBR30OUT-A)

BR30 Flood Light Bulb Bluetooth Compatible (Outdoor Bulb Sold Separately)





RGBW LED Light Bulb INDOOR USE (DS-RGB-A19-A)

Everyday A19 Replacement Light Bulb Bluetooth Compatible




















4.5"

Smart RGBW LED MR16 SMALL (DS-RGBMR16SMSW-A) Bluetooth Compatible

Smart RGBW LED MR16 LARGE (DS-RGBMR16LG-A) Bluetooth Compatible

Smart RGBW LED PAR36
OUTDOOR USE
(DS-RGBPAR36-A)
Bluetooth Compatible





Demo Kit




NTD Demo Kit NTD-LIGHTSDEMOKIT-A

Quickly and easily showcase how landscape lighting can transform your customers' property. Immediately reposition lights anywhere or turn them on/off individually with the Decor Smart app.











RGB LED Bistro Lights (DS-RGBBISTRO24, DS-RGBBISTRO48)

Suspender Light String with 24" Spacing, 12 Bulbs, 110V with Control Module Bluetooth Compatible (24" & 48" Extension Sold Separately)







RGBW Wash Light

80W/180W (DS-RGBWPAN80W45, DS-RGBWPAN180W45, DS-RGBWPAN180W12, DS-RGBWPAN80W12, DS-RGBWPAN180W24)

(Each sold separately)



RGBW Wash Light

(DS-RGBBAR72W15, DS-RGBBAR72W45, DS-RGBBAR72W30)

(Each sold separately)





RGBW Inground Wash Light

(DS-RGBWINGD18W15, DS-RGBWINGD18W30, DS-RGBWINGD18W60)

(Each sold separately)



200W Transformer for Decor Smart/PL Lighting with Spike Cube

DS-200WTRANS-K

Quickly and easily showcase how landscape lighting can transform your customers' property. Immediately reposition lights anywhere or turn them on/off individually with the Decor Smart app.











RGB Smart Light Remote (DS-RGBREMOTE)
Remote for RGB Smart Lights



Smart Socket/Repeater
15A
(DS-SMARTSOCKET)

(Each sold separately)



RGB BT Repeater MT 4Wire (PL-RGBREP4)

Repeater to use with Decor Smart RGB Products



Wifi/Bluetooth Gateway CLOUD MANAGEMENT (DS-GATEWAY)

Bluetooth and Wifi Compatible Gateway for RGB Smart Lights



Digital Astro Timer Controller

18W (ASTROTIMER-CONTROLLER)

(Each sold separately)



Decor Smart Astro Timer Controller

18W (DS-ASTROTIMERV2)

(Each sold separately)





Permalites® 365 are the best way to celebrate your special occasions by creating any color pattern you want! Whether you're celebrating America's Independence or Santa's return for

Christmas, the possibilites are endless!

Permalites® 365 offers the opportunity
to promote your business by attracting
customers with your unique lighting patterns!

PATENTED TRACK SYSTEM

Permalites® patented track system protects components and hides them from view during the day. The crown moulding style cover is available in several colors that allow this product to blend in with the installation surface.



TRACK COLORS



COVERS/LIDS





With a wide selection of features, Permalites® 365 are a great way to promote your business!

CUSTOM EFFECTS



Celebrate every special occasion with Permalites® 365 custom effects and light patterns. The Decor Smart app helps you instantly create any color pattern you want to display on your building.

HOLIDAY LIGHTING



From Christmas to Halloween, Permalites® 365 has custom presets for every holiday in the year. For those fun nights and special events, easily change the colors of the presets in the Decor Smart app to match the mood you're looking for.

BRIGHT & EFFICIENT



Permalites® 365 are brighter and longer lasting than any light on the market. Your building will shine the brightest out of everyone around you. Using less than .5 watt per light Permalites® 365 are very efficient at conserving energy.

SECURITY LIGHTING



Keep your business and clients safe by having bright lights around your building that deter unwanted visitors. Be comfortable in your environment knowing you have full-sight outside your doors and windows.

DURABLE DESIGN



Permalites® 365 are designed to withstand all types of weather environments for years of enjoyment.

BEST COLOR ACCURACY



Permalites® 365 has access to millions of colors that display every shade of color you can imagine. The possibilities are endless when you use the Decor Smart app to create every color combination you want.





HOLIDAY LIGHTING

Your Permalites® 365 are packed with holiday lighting effects such as Christmas, Easter, Independence Day, and more! Now you can show your pride or holiday spirit with a push of a button!







ENDLESS POSSIBILITIES

No matter how you use your new Permalites® 365 system, you will always have a fascinating result. Bring your business or city to life with color and enjoy the wonderful experience of having color changing lights all year long!



New Products

Our new products include updated hardware and new features



12VAC/DC Controller with Dimmer (DS-12V-CONTDIM)
New decorsmart controller with dimmer 120 watts output



PWM Signal Controller (DS-RGBWPWMCONT) PWM Signal Controller RGG Flood & Wash Lights



MT Bluetooth Repeater (PL-RGBREP4)
Bluetooth repeater with 3 connections PL, RGB+, Power Supply



4 Wire Controller (PL-DIGCONT2P)
2 Output MT 4 Wire Controller



Smart T-Way (DS-RGBWSMARTT) Smart T-way for individual wall wash control



Photometrics Charts

Photometrics gauges how humans perceive light-its coverage area, i.e., where light cuts off, where its lost and the intensity of light in relation to distance from the light source. In practical terms, photometrics shows whether a lighting plan meets the quantitive lighting requirements for a project.

MR 11 2.5W

MR11 2.5W 2700K 24° 2.5W CANDLEPOWER: 167.65						
Distance	Foot	Candles				
2ft	11"	1461.79				
4ft	1'10"	365.45				
6ft	2'9"	162.42				
8ft	3'8"	91.36				
10ft	4'7"	58.47				
15ft	6'11"	25.99				
20ft	9'2"	14.62				
30ft	13'10"	6.50				
40ft	18'5"	3.65				
50ft	23"	2.34				

MR11 2.5W 2700K 38° 2.5W CANDLEPOWER:167.66						
Distance	Foot	Candles				
2ft	1'5"	824.87				
4ft	2'11"	206.22				
6ft	4'5"	91.65				
8ft	5'10"	51.55				
10ft	7'4"	32.99				
15ft	10'11"	14.66				
20ft	14'7"	8.25				
30ft	21'11"	3.67				
40ft	29'2"	2.06				
50ft	36'6"	1.32				

MR11 2.5W 2700K 60° 2.5W CANDLEPOWER: 159.983						
Distance	Foot	Candles				
2ft	2'4"	407.10				
4ft	4'8"	101.78				
6ft	7'	45.23				
8ft	9'4"	25.44				
10ft	11'8"	16.28				
15ft	17'6"	7.24				
20ft	23'5"	4.07				
30ft	35'1"	1.81				
40ft	46'9"	1.02				
50ft	58'6"	0.65				

MR11 2.5W 2700K 120° 2.5W CANDLEPOWER: 124.904					
Distance	Distance Foot				
2ft	5'5"	121.85			
4ft	10'10"	30.46			
6ft	16'3"	13.54			
8ft	21'8"	7.62			
10ft	27'1"	4.87			
15ft	40'7"	2.17			
20ft	54'2"	1.22			
30ft	81'3"	0.54			
40ft	108'4"	0.30			
50ft	135'5"	0.19			

MR11 2.5W 3000K 24° 2.5W CANDLEPOWER: 175.50						
Distance	Foot	Candles				
2ft	11"	1530.23				
4ft	1'10"	382.56				
6ft	2'9"	170.03				
8ft	3'8"	95.64				
10ft	4'7"	61.21				
15ft	6'11"	27.20				
20ft	9'2"	15.30				
30ft	13'10"	6.80				
40ft	18'5"	3.83				
50ft	23"	2.45				

MR11 2.5W 3000K 38° 2.5W CANDLEPOWER:170.52						
Distance	Foot	Candles				
2ft	1'5"	838.97				
4ft	2'11"	209.74				
6ft	4'5"	93.22				
8ft	5'10"	52.44				
10ft	7'4"	33.56				
15ft	10'11"	14.91				
20ft	14'7"	8.39				
30ft	21'11"	3.73				
40ft	29'2"	2.10				
50ft	36'6"	1.34				

MR11 2.5W 3000K 60° 2.5W CANDLEPOWER: 169.3						
Distance	Foot	Candles				
2ft	2'4"	430.79				
4ft	4'8"	107.70				
6ft	7'	47.87				
8ft	9'4"	26.92				
10ft	11'8"	17.23				
15ft	17'6"	7.66				
20ft	23'5"	4.31				
30ft	35'1"	1.91				
40ft	46'9"	1.08				
50ft	58'6"	0.69				

MR11 2.5W 3000K 120° 2.5W CANDLEPOWER: 138.404		
Foot	Candles	
5'5"	134.98	
10'10"	33.75	
16'3"	15.00	
21'8"	8.44	
27'1"	5.40	
40'7"	2.40	
54'2"	1.35	
81'3"	0.60	
108'4"	0.34	
135'5"	0.22	
	Foot 5'5" 10'10" 16'3" 21'8" 27'1" 40'7" 54'2" 81'3" 108'4"	

MR11 2.5W 5000K 24° 2.5W CANDLEPOWER:195.52		
Distance	Foot	Candles
2ft	11"	1704.81
4ft	1'10"	426.20
6ft	2'9"	189.42
8ft	3'8"	106.55
10ft	4'7"	68.19
15ft	6'11"	30.31
20ft	9'2"	17.05
30ft	13'10"	7.58
40ft	18'5"	4.26
50ft	23"	2.73

MR11 2.5W 5000K 38° 2.5W CANDLEPOWER:189.13		
Distance	Foot	Candles
2ft	1'5"	930.57
4ft	2'11"	232.64
6ft	4'5"	103.40
8ft	5'10"	58.16
10ft	7'4"	37.22
15ft	10'11"	16.54
20ft	14'7"	9.31
30ft	21'11"	4.14
40ft	29'2"	2.33
50ft	36'6"	1.49

MR11 2.5W 5000K 60° 2.5W CANDLEPOWER:180.9		
Distance	Foot	Candles
2ft	2'4"	460.28
4ft	4'8"	115.07
6ft	7'	51.14
8ft	9'4"	28.77
10ft	11'8"	18.41
15ft	17'6"	8.18
20ft	23'5"	4.60
30ft	35'1"	2.05
40ft	46'9"	1.15
50ft	58'6"	0.74

MR11 2.5W 5000K 120° 2.5W CANDLEPOWER:155.5		
Distance	Foot	Candles
2ft	5'5"	151.67
4ft	10'10"	37.92
6ft	16'3"	16.85
8ft	21'8"	9.48
10ft	27'1"	6.07
15ft	40'7"	2.70
20ft	54'2"	1.52
30ft	81'3"	0.67
40ft	108'4"	0.38
50ft	135'5"	0.24

MR 16 4W

MR16 4W 2700K 15° 4W CANDLEPOWER:323.96		
Distance	Foot	Candles
2ft	9"	2807.32
4ft	1'6"	701.83
6ft	2'3"	311.92
8ft	2'12"	175.46
10ft	3'9"	112.29
15ft	5'7"	49.91
20ft	7'6"	28.07
30ft	11'1"	12.48
40ft	14'11"	7.02
50ft	18'8"	4.49

MR16 4W 2700K 30° 4W CANDLEPOWER: 359.18		
Distance	Foot	Candles
2ft	1'1"	2508.07
4ft	2'3"	627.02
6ft	3'5"	278.67
8ft	4'7"	156.75
10ft	5'8"	100.32
15ft	8'6"	44.59
20ft	11'5"	25.08
30ft	17'1"	11.15
40ft	22'9"	6.27
50ft	28'6"	4.01

MR16 4W 2700K 45° 4W CANDLEPOWER: 363.783		
Distance	Foot	Candles
2ft	1'6"	1574.81
4ft	3'1"	393.70
6ft	4'7"	174.98
8ft	6'1"	98.43
10ft	7'7"	62.99
15ft	11'4"	28.00
20ft	15'2"	15.75
30ft	22'9"	7.00
40ft	30'3"	3.94
50ft	37'10"	2.52

MR16 4W 2700K 60° 4W CANDLEPOWER: 370.76		
Distance	Foot	Candles
2ft	2'3"	908.18
4ft	4'6"	227.05
6ft	6'10"	100.91
8ft	9'1"	56.76
10ft	11'4"	36.33
15ft	17'1"	16.15
20ft	22'8"	9.08
30ft	34'1"	4.04
40ft	45'5"	2.27
50ft	56'9"	1.45

MR16 4W 2700K 100° 4W CANDLEPOWER: 312.84		
Distance	Foot	Candles
2ft	4'9"	313.78
4ft	9'5"	78.44
6ft	14'2"	34.86
8ft	18'11"	19.61
10ft	23'7"	12.55
15ft	35'5"	5.58
20ft	47'3"	3.14
30ft	70'10"	1.39
40ft	94'5"	0.78
50ft	118'1"	0.50

MR16 4W 3000K 15° 4W CANDLEPOWER:345.95		
Distance	Foot	Candles
2ft	9"	2997.85
4ft	1'6"	749.46
6ft	2'3"	333.09
8ft	2'12"	187.37
10ft	3'9"	119.91
15ft	5'7"	53.30
20ft	7'6"	29.98
30ft	11'1"	13.32
40ft	14'11"	7.49
50ft	18'8"	4.80

MR16 4W 3000K 30° 4W CANDLEPOWER: 361.32		
Distance	Foot	Candles
2ft	1'1"	2523.04
4ft	2'3"	630.76
6ft	3'5"	280.34
8ft	4'7"	157.69
10ft	5'8"	100.92
15ft	8'6"	44.85
20ft	11'5"	25.23
30ft	17'1"	11.21
40ft	22'9"	6.31
50ft	28'6"	4.04

MR16 4W 3000K 45° 4W CANDLEPOWER: 382.10		
Distance	Foot	Candles
2ft	1'6"	1669.54
4ft	3'1"	417.38
6ft	4'7"	185.50
8ft	6'1"	104.35
10ft	7'7"	66.78
15ft	11'4"	29.68
20ft	15'2"	16.70
30ft	22'9"	7.42
40ft	30'3"	4.17
50ft	37'10"	2.67

MR16 4W 3000K 60° 4W CANDLEPOWER: 390.67		
Distance	Foot	Candles
2ft	2'3"	956.94
4ft	4'6"	239.24
6ft	6'10"	106.33
8ft	9'1"	59.81
10ft	11'4"	38.28
15ft	17'1"	17.01
20ft	22'8"	9.57
30ft	34'1"	4.25
40ft	45'5"	2.39
50ft	56'9"	1.53

MR16 4W 2700K 100° 4W CANDLEPOWER: 330.56		
Distance	Foot	Candles
2ft	4'9"	331.54
4ft	9'5"	82.88
6ft	14'2"	36.84
8ft	18'11"	20.72
10ft	23'7"	13.26
15ft	35'5"	5.89
20ft	47'3"	3.32
30ft	70'10"	1.47
40ft	94'5"	0.83
50ft	118'1"	0.53

MR16 4W 5000K 15° 4W CANDLEPOWER:385.12		
Distance	Foot	Candles
2ft	9"	3337.24
4ft	1'6"	834.31
6ft	2'3"	370.80
8ft	2'12"	208.58
10ft	3'9"	133.49
15ft	5'7"	59.33
20ft	7'6"	33.37
30ft	11'1"	14.83
40ft	14'11"	8.34
50ft	18'8"	5.34

MR16 4W 5000K 30° 4W CANDLEPOWER: 379.10		
Distance	Foot	Candles
2ft	1'1"	2647.15
4ft	2'3"	661.79
6ft	3'5"	294.13
8ft	4'7"	165.45
10ft	5'8"	105.89
15ft	8'6"	47.06
20ft	11'5"	26.47
30ft	17'1"	11.77
40ft	22'9"	6.62
50ft	28'6"	4.24

MR16 4W 5000K 45° 4W CANDLEPOWER: 400.21		
Distance	Foot	Candles
2ft	1'6"	1748.65
4ft	3'1"	437.16
6ft	4'7"	194.29
8ft	6'1"	109.29
10ft	7'7"	69.95
15ft	11'4"	31.09
20ft	15'2"	17.49
30ft	22'9"	7.77
40ft	30'3"	4.37
50ft	37'10"	2.80

MR16 4W 5000K 60° 4W CANDLEPOWER: 410.93		
Distance	Foot	Candles
2ft	2'3"	1006.57
4ft	4'6"	251.64
6ft	6'10"	111.84
8ft	9'1"	62.91
10ft	11'4"	40.26
15ft	17'1"	17.89
20ft	22'8"	10.07
30ft	34'1"	4.47
40ft	45'5"	2.52
50ft	56'9"	1.61

MR16 4W 5000K 100° 4W CANDLEPOWER: 340.161		
Distance	Foot	Candles
2ft	4'9"	341.23
4ft	9'5"	85.31
6ft	14'2"	37.91
8ft	18'11"	21.33
10ft	23'7"	13.65
15ft	35'5"	6.07
20ft	47'3"	3.41
30ft	70'10"	1.52
40ft	94'5"	0.85
50ft	118'1"	0.55

MR 16 5W

MR16 2700K 15° 5W CANDLEPOWER: 525.78		
Distance	Foot	Candles
2ft	9"	9483.21
4ft	1'5"	2370.80
6ft	2'3"	1053.69
8ft	2'11"	592.70
10ft	3'8"	379.33
15ft	5'6"	168.59
20ft	7'4"	94.83
30ft	11'	42.15
40ft	14'8"	23.71
50ft	18'5"	15.17

MR16 2700K 30° 5W CANDLEPOWER: 478.995		
Distance	Foot	Candles
2ft	11"	4128.12
4ft	1'10"	1032.03
6ft	2'10"	458.68
8ft	3'9"	258.01
10ft	4'8"	165.12
15ft	7'1"	73.39
20ft	9'5"	41.28
30ft	14'2"	18.35
40ft	18'10"	10.32
50ft	23'7"	6.60

MR16 2700K 45° 5W CANDLEPOWER:439.56		
Distance	Foot	Candles
2ft	1'4"	2839.61
4ft	2'8"	709.90
6ft	3'11"	315.51
8ft	5'3"	177.48
10ft	6'7"	113.58
15ft	9'10"	50.48
20ft	13'2"	28.40
30ft	19'8"	12.62
40ft	26'3"	7.10
50ft	32'10"	4.54

MR16 2700K 60° 5W CANDLEPOWER: 466.734		
Distance	Foot	Candles
2ft	2'1"	1409.90
4ft	4'2"	352.48
6ft	6'3"	156.66
8ft	8'4"	88.12
10ft	10'5"	56.40
15ft	15'7"	25.06
20ft	20'9"	14.10
30ft	31'2"	6.27
40ft	41'7"	3.52
50ft	51'11"	2.26

MR16 2700K 120° 5W CANDLEPOWER: 375.89		
Distance	Foot	Candles
2ft	5'8"	321.64
4ft	11'5"	80.41
6ft	17'2"	35.74
8ft	22'10"	20.10
10ft	28'7"	12.87
15ft	42'10"	5.72
20ft	57'2"	3.22
30ft	85'8"	1.43
40ft	114'4"	0.80
50ft	142'9"	0.51

MR16 3000K 15° 5W CANDLEPOWER: 535.23		
Distance	Foot	Candles
2ft	9"	9653.61
4ft	1'5"	2413.40
6ft	2'3"	1072.62
8ft	2'11"	603.35
10ft	3'8"	386.14
15ft	5'6"	171.62
20ft	7'4"	96.54
30ft	11'	42.90
40ft	14'8"	24.13
50ft	18'5"	15.45

MR16 3000K 30° 5W CANDLEPOWER: 490.5		
Distance	Foot	Candles
2ft	11"	4227.23
4ft	1'10"	1056.81
6ft	2'10"	469.69
8ft	3'9"	264.20
10ft	4'8"	169.09
15ft	7'1"	75.15
20ft	9'5"	42.27
30ft	14'2"	18.79
40ft	18'10"	10.57
50ft	23'7"	6.76

MR16 3000K 45° 5W CANDLEPOWER:452.63		
Distance	Foot	Candles
2ft	1'4"	2924.00
4ft	2'8"	731.00
6ft	3'11"	324.89
8ft	5'3"	182.75
10ft	6'7"	116.96
15ft	9'10"	51.98
20ft	13'2"	29.24
30ft	19'8"	13.00
40ft	26'3"	7.31
50ft	32'10"	4.68

MR16 3000K 60° 5W CANDLEPOWER: 489.125		
Distance	Foot	Candles
2ft	2'1"	1477.50
4ft	4'2"	369.38
6ft	6'3"	164.17
8ft	8'4"	92.34
10ft	10'5"	59.10
15ft	15'7"	26.27
20ft	20'9"	14.78
30ft	31'2"	6.57
40ft	41'7"	3.69
50ft	51'11"	2.36

MR16 3000K 120° 5W CANDLEPOWER: 389.55		
Distance	Foot	Candles
2ft	5'8"	324.22
4ft	11'5"	81.05
6ft	17'2"	36.02
8ft	22'10"	20.26
10ft	28'7"	12.97
15ft	42'10"	5.76
20ft	57'2"	3.24
30ft	85'8"	1.44
40ft	114'4"	0.81
50ft	142'9"	0.52

MR16 5000K 15° 5W CANDLEPOWER: 540.51		
Distance	Foot	Candles
2ft	9"	9748.87
4ft	1'5"	2437.22
6ft	2'3"	1083.21
8ft	2'11"	609.30
10ft	3'8"	389.95
15ft	5'6"	173.31
20ft	7'4"	97.49
30ft	11'	43.33
40ft	14'8"	24.37
50ft	18'5"	15.60

MR16 5000K 30° 5W CANDLEPOWER: 530.415		
Distance	Foot	Candles
2ft	11"	4571.26
4ft	1'10"	1142.81
6ft	2'10"	507.92
8ft	3'9"	285.70
10ft	4'8"	182.85
15ft	7'1"	81.27
20ft	9'5"	45.71
30ft	14'2"	20.32
40ft	18'10"	11.43
50ft	23'7"	7.31

MR16 5000K 45° 5W CANDLEPOWER:470.78		
Distance	Foot	Candles
2ft	1'4"	3041.23
4ft	2'8"	760.31
6ft	3'11"	337.91
8ft	5'3"	190.08
10ft	6'7"	121.65
15ft	9'10"	54.07
20ft	13'2"	30.41
30ft	19'8"	13.52
40ft	26'3"	7.60
50ft	32'10"	4.87

MR16 5000K 60° 5W CANDLEPOWER: 506.312		
Distance	Foot	Candles
2ft	2'1"	1529.39
4ft	4'2"	382.35
6ft	6'3"	169.93
8ft	8'4"	95.59
10ft	10'5"	61.18
15ft	15'7"	27.19
20ft	20'9"	15.29
30ft	31'2"	6.80
40ft	41'7"	3.82
50ft	51'11"	2.45

MR16 5000K 120° 5W CANDLEPOWER: 400.5		
Distance	Foot	Candles
2ft	5'8"	341.55
4ft	11'5"	85.39
6ft	17'2"	37.95
8ft	22'10"	21.35
10ft	28'7"	13.66
15ft	42'10"	6.07
20ft	57'2"	3.42
30ft	85'8"	1.52
40ft	114'4"	0.85
50ft	142'9"	0.55

MR 16 7W

MR16 7W 2700K 15° CANDLEPOWER: 682.21		
Distance	Foot	Candles
2ft	8"	8799.79
4ft	1'5"	2199.95
6ft	2'1"	977.75
8ft	2'10"	549.99
10ft	3'16"	351.99
15ft	5'4"	156.44
20ft	7'1"	88.00
30ft	10'7"	39.11
40ft	14'2"	22.00
50ft	17'8"	14.08

MR16 7W 2700K 30° CANDLEPOWER: 627.822		
Distance	Foot	Candles
2ft	1'5"	4744.89
4ft	2'1"	1186.22
6ft	3'2"	527.21
8ft	4'2"	296.56
10ft	5'2"	189.80
15ft	7'10"	84.35
20ft	10'1"	47.45
30ft	15'8"	21.09
40ft	20'10"	11.86
50ft	26'1"	7.59

MR16 7W 2700K 45° CANDLEPOWER: 610.985		
Distance	Foot	Candles
2ft	1'8"	2673.09
4ft	3'4"	668.27
6ft	4'12"	297.01
8ft	6'8"	167.07
10ft	8'4"	106.92
15ft	12'6"	47.52
20ft	16'8"	26.73
30ft	24'12"	11.88
40ft	33'4"	6.68
50ft	41'8"	4.28

MR16 7W 2700K 60° CANDLEPOWER: 609.417		
Distance	Foot	Candles
2ft	2'4"	1487.30
4ft	4'7"	371.82
6ft	6'11"	165.26
8ft	9'3"	92.96
10ft	11'6"	59.49
15ft	17'3"	26.44
20ft	23'	14.87
30ft	34'7"	6.61
40ft	46'1"	3.72
50ft	57'7"	2.38

MR16 7W 2700K 120° CANDLEPOWER: 399.2		
Distance	Foot	Candles
2ft	5'10"	340.47
4ft	11'7"	85.12
6ft	17'5"	37.83
8ft	23'4"	21.28
10ft	29'1"	13.62
15ft	43'8"	6.05
20ft	58'2"	3.40
30ft	87'4"	1.51
40ft	116'5"	0.85
50ft	145'6"	0.54

MR16 7W 3000K 15° CANDLEPOWER: 695.523		
Distance	Foot	Candles
2ft	8"	8971.91
4ft	1'5"	2242.98
6ft	2'1"	996.88
8ft	2'10"	560.74
10ft	3'16"	358.88
15ft	5'4"	159.50
20ft	7'1"	89.72
30ft	10'7"	39.88
40ft	14'2"	22.43
50ft	17'8"	14.36
-		

MR16 7W 3000K 30° CANDLEPOWER: 647.856		
Distance	Foot	Candles
2ft	1'5"	4825.83
4ft	2'1"	1206.46
6ft	3'2"	536.20
8ft	4'2"	301.61
10ft	5'2"	193.03
15ft	7'10"	85.79
20ft	10'1"	48.26
30ft	15'8"	21.45
40ft	20'10"	12.06
50ft	26'1"	7.72

MR16 7W 3000K 45° CANDLEPOWER: 625.655		
Distance	Foot	Candles
2ft	1'8"	2765.34
4ft	3'4"	691.33
6ft	4'12"	307.26
8ft	6'8"	172.83
10ft	8'4"	110.61
15ft	12'6"	49.16
20ft	16'8"	27.65
30ft	24'12"	12.29
40ft	33'4"	6.91
50ft	41'8"	4.42

MR16 7W 3000K 60° CANDLEPOWER: 620.899		
Distance	Foot	Candles
2ft	2'4"	1515.29
4ft	4'7"	378.82
6ft	6'11"	168.37
8ft	9'3"	94.71
10ft	11'6"	60.61
15ft	17'3"	26.94
20ft	23'	15.15
30ft	34'7"	6.73
40ft	46'1"	3.79
50ft	57'7"	2.42

MR16 7W 3000K 120° CANDLEPOWER: 410.89		
Distance	Foot	Candles
2ft	5'10"	350.48
4ft	11'7"	87.62
6ft	17'5"	38.94
8ft	23'4"	21.91
10ft	29'1"	14.02
15ft	43'8"	6.23
20ft	58'2"	3.50
30ft	87'4"	1.56
40ft	116'5"	0.88
50ft	145'6"	0.56

MR16 7W 5000K 15° CANDLEPOWER: 700.891		
Distance	Foot	Candles
2ft	8"	9041.12
4ft	1'5"	2260.28
6ft	2'1"	1004.57
8ft	2'10"	565.07
10ft	3'16"	361.64
15ft	5'4"	160.73
20ft	7'1"	90.41
30ft	10'7"	40.18
40ft	14'2"	22.60
50ft	17'8"	14.47

MR16 7W 5000K 30° CANDLEPOWER: 669.765		
Distance	Foot	Candles
2ft	1'5"	4910.98
4ft	2'1"	1227.74
6ft	3'2"	545.66
8ft	4'2"	306.94
10ft	5'2"	196.44
15ft	7'10"	87.31
20ft	10'1"	49.11
30ft	15'8"	21.83
40ft	20'10"	12.28
50ft	26'1"	7.86

MR16 7W 5000K 45° CANDLEPOWER: 650.325		
Distance	Foot	Candles
2ft	1'8"	2874.38
4ft	3'4"	718.60
6ft	4'12"	319.38
8ft	6'8"	179.65
10ft	8'4"	114.98
15ft	12'6"	51.10
20ft	16'8"	28.74
30ft	24'12"	12.78
40ft	33'4"	7.19
50ft	41'8"	4.60

MR16 7W 5000K 60° CANDLEPOWER: 640.763		
Distance	Foot	Candles
2ft	2'4"	1563.72
4ft	4'7"	390.93
6ft	6'11"	173.75
8ft	9'3"	97.73
10ft	11'6"	62.55
15ft	17'3"	27.80
20ft	23'	15.64
30ft	34'7"	6.95
40ft	46'1"	3.91
50ft	57'7"	2.50

MR16 7W 5000K 120° CANDLEPOWER: 420.5			
Foot	Candles		
5'10"	358.67		
11'7"	89.67		
17'5"	39.85		
23'4"	22.42		
29'1"	14.35		
43'8"	6.38		
58'2"	3.59		
87'4"	1.59		
116'5"	0.90		
145'6"	0.57		
	Foot 5'10" 11'7" 17'5" 23'4" 29'1" 43'8" 58'2" 87'4" 116'5"		

PAR 36 6W

PAR36 6W 2700K 15° CANDLEPOWER: 536.774		
Distance	Foot	Candles
2ft	7"	9679.23
4ft	1'2"	2419.81
6ft	1'9"	1075.47
8ft	2'4"	604.95
10ft	2'11"	387.17
15ft	4'4"	172.08
20ft	5'10"	96.79
30ft	8'9"	43.02
40ft	11'8"	24.20
50ft	14'7"	15.49

PAR36 6W 2700K 24° CANDLEPOWER: 622.86		
Distance	Foot	Candles
2ft	9"	6558.67
4ft	1'7"	1639.67
6ft	2'5"	728.74
8ft	3'3"	409.92
10ft	4'1"	262.35
15ft	6'1"	116.60
20ft	8'8"	65.59
30ft	12'1"	29.15
40ft	16'2"	16.40
50ft	20'2"	10.49

PAR36 6W 2700K 38° CANDLEPOWER: 594.95		
Distance	Foot	Candles
2ft	1'4"	3534.98
4ft	2'7"	883.75
6ft	3'11"	392.78
8ft	5'3"	220.94
10ft	6'6"	141.40
15ft	9'9"	62.84
20ft	13'1"	35.35
30ft	19'17"	15.71
40ft	26'1"	8.84
50ft	32'7"	5.66

PAR36 6W 2700K 60° CANDLEPOWER: 532.653		
Distance	Foot	Candles
2ft	1'11"	1623.14
4ft	3'11"	405.79
6ft	5'10"	180.35
8ft	7'10"	101.45
10ft	9'9"	64.93
15ft	14'8"	28.86
20ft	19'7"	16.23
30ft	29'4	7.21
40ft	39'1"	4.06
50ft	48'11"	2.60

PAR36 6W 2700K 120° CANDLEPOWER: 378.661		
Distance	Foot	Candles
2ft	6'8"	321.31
4ft	13'5"	80.33
6ft	20'1"	35.70
8ft	26'9"	20.08
10ft	33'6"	12.85
15ft	50'3"	5.71
20ft	66'1"	3.21
30ft	100'5"	1.43
40ft	133'11"	0.80
50ft	167'5"	0.51

PAR36 6W 3000K 15° CANDLEPOWER: 545.75		
Foot	Candles	
7"	9841.12	
1'2"	2460.28	
1'9"	1093.46	
2'4"	615.07	
2'11"	393.64	
4'4"	174.95	
5'10"	98.41	
8'9"	43.74	
11'8"	24.60	
14'7"	15.75	
	Foot 7" 1'2" 1'9" 2'4" 2'11" 4'4" 5'10" 8'9" 11'8"	

PAR36 6W 3000K 24° CANDLEPOWER:640.85		
Distance	Foot	Candles
2ft	9"	6748.12
4ft	1'6"	1687.03
6ft	2'3"	749.79
8ft	2'11"	421.76
10ft	3'8"	269.92
15ft	5'7"	119.97
20ft	7'5"	67.48
30ft	11'1"	29.99
40ft	14'10"	16.87
50ft	18'6"	10.80

PAR36 6W 3000K 38° CANDLEPOWER: 620.12		
Distance	Foot	Candles
2ft	1'4"	3684.50
4ft	2'7"	921.12
6ft	3'11"	409.39
8ft	5'3"	230.28
10ft	6'6"	147.38
15ft	9'9"	65.50
20ft	13'1"	36.84
30ft	19'17"	16.38
40ft	26'1"	9.21
50ft	32'7"	5.90

PAR36 6W 3000K 60° CANDLEPOWER: 541.65		
Distance	Foot	Candles
2ft	1'11"	1650.59
4ft	3'11"	412.65
6ft	5'10"	183.40
8ft	7'10"	103.16
10ft	9'9"	66.02
15ft	14'8"	29.34
20ft	19'7"	16.51
30ft	29'4	7.34
40ft	39'1"	4.13
50ft	48'11"	2.64

PAR36 6W 3000K 120° CANDLEPOWER: 415.96		
Distance	Foot	Candles
2ft	6'8"	352.96
4ft	13'5"	88.24
6ft	20'1"	39.22
8ft	26'9"	22.06
10ft	33'6"	14.12
15ft	50'3"	6.27
20ft	66'1"	3.53
30ft	100'5"	1.57
40ft	133'11"	0.88
50ft	167'5"	0.56

PAR36 6W 5000K 15° CANDLEPOWER: 559.59		
Distance	Foot	Candles
2ft	7"	10090.64
4ft	1'2"	2522.66
6ft	1'9"	1121.18
8ft	2'4"	630.66
10ft	2'11"	403.63
15ft	4'4"	179.39
20ft	5'10"	100.91
30ft	8'9"	44.85
40ft	11'8"	25.23
50ft	14'7"	16.15

PAR36 6W 5000K 24° CANDLEPOWER: 651.23		
Distance	Foot	Candles
2ft	9"	6857.37
4ft	1'6"	1714.34
6ft	2'3"	761.93
8ft	2'11"	428.59
10ft	3'8"	274.29
15ft	5'7"	121.91
20ft	7'5"	68.57
30ft	11'1"	30.48
40ft	14'10"	17.14
50ft	18'6"	10.97

PAR36 6W 5000K 38° CANDLEPOWER: 635.89		
Distance	Foot	Candles
2ft	1'4"	3778.15
4ft	2'7"	944.54
6ft	3'11"	419.79
8ft	5'3"	236.13
10ft	6'6"	151.13
15ft	9'9"	67.17
20ft	13'1"	37.78
30ft	19'17"	16.79
40ft	26'1"	9.45
50ft	32'7"	6.05

PAR36 6W 5000K 60° CANDLEPOWER: 566.90		
Distance	Foot	Candles
2ft	1'11"	1727.45
4ft	3'11"	431.86
6ft	5'10"	191.94
8ft	7'10"	107.97
10ft	9'9"	69.10
15ft	14'8"	30.71
20ft	19'7"	17.27
30ft	29'4	7.68
40ft	39'1"	4.32
50ft	48'11"	2.76

PAR36 6W 5000K 120° CANDLEPOWER: 436.98		
Distance	Foot	Candles
2ft	6'8"	370.83
4ft	13'5"	92.71
6ft	20'1"	41.20
8ft	26'9"	23.18
10ft	33'6"	14.83
15ft	50'3"	6.59
20ft	66'1"	3.71
30ft	100'5"	1.65
40ft	133'11"	0.93
50ft	167'5"	0.59

PAR 36 10W

PAR36 10W 2700K 15° CANDLEPOWER: 1000.12		
Distance	Foot	Candles
2ft	5"	13928.96
4ft	11"	3482.24
6ft	1'4"	1547.66
8ft	1'9"	870.56
10ft	2'3"	557.16
15ft	3'4"	247.63
20ft	4'5"	139.29
30ft	6'8"	61.91
40ft	8'11"	34.82
50ft	11'1"	22.29

PAR36 10W 2700K 24° CANDLEPOWER: 975.5		
Distance	Foot	Candles
2ft	10"	12362.43
4ft	1'7"	3090.61
6ft	2'5"	1373.60
8ft	3'3"	772.65
10ft	4'1"	494.50
15ft	6'1"	219.78
20ft	8'1"	123.62
30ft	12'1"	54.94
40ft	16'2"	30.91
50ft	20'2"	19.78

PAR36 10W 2700K 38° CANDLEPOWER: 952.63		
Distance	Foot	Candles
2ft	1'3"	3440.26
4ft	2'7"	860.06
6ft	3'10"	382.25
8ft	5'1"	215.02
10ft	6'5"	137.61
15ft	9'7"	61.16
20ft	12'9"	34.40
30ft	19'2"	15.29
40ft	25'7"	8.60
50ft	31'12"	5.50

PAR36 10W 2700K 60° CANDLEPOWER: 936.532		
Distance	Foot	Candles
2ft	1'11"	3009.90
4ft	3'9"	752.48
6ft	5'8"	334.43
8ft	7'7"	188.12
10ft	9'6"	120.40
15ft	14'3"	53.51
20ft	18'12"	30.10
30ft	28'6"	13.38
40ft	37'12"	7.52
50ft	47'6"	4.82

PAR36 10W 2700K 120° CANDLEPOWER: 586.91		
Distance	Foot	Candles
2ft	6'8"	500.54
4ft	13'3"	125.13
6ft	19'11"	55.62
8ft	26'7"	31.28
10ft	33'3"	20.02
15ft	49'10"	8.90
20ft	66'5"	5.01
30ft	99'8"	2.22
40ft	132'11"	1.25
50ft	166'1"	0.80

PAR36 10W 3000K 15° CANDLEPOWER: 1013.56		
Distance	Foot	Candles
2ft	5"	14116.15
4ft	11"	3529.04
6ft	1'4"	1568.46
8ft	1'9"	882.26
10ft	2'3"	564.65
15ft	3'4"	250.95
20ft	4'5"	141.16
30ft	6'8"	62.74
40ft	8'11"	35.29
50ft	11'1"	22.59

PAR36 10W 3000K 24° CANDLEPOWER: 987.5		
Distance	Foot	Candles
2ft	10"	12514.53
4ft	1'7"	3128.63
6ft	2'5"	1390.50
8ft	3'3"	782.16
10ft	4'1"	500.58
15ft	6'1"	222.48
20ft	8'1"	125.15
30ft	12'1"	55.62
40ft	16'2"	31.29
50ft	20'2"	20.02

PAR36 10W 3000K 38° CANDLEPOWER: 970.23		
Distance	Foot	Candles
2ft	1'3"	3503.77
4ft	2'7"	875.94
6ft	3'10"	389.31
8ft	5'1"	218.99
10ft	6'5"	140.15
15ft	9'7"	62.29
20ft	12'9"	35.04
30ft	19'2"	15.57
40ft	25'7"	8.76
50ft	31'12"	5.61

PAR36 10W 3000K 60° CANDLEPOWER: 955.463				
Distance	Distance Foot Candles			
2ft	1'11"	3070.72		
4ft	3'9"	767.68		
6ft	5'8"	341.19		
8ft	7'7"	191.92		
10ft	9'6"	122.83		
15ft	14'3"	54.59		
20ft	18'12"	30.71		
30ft	28'6"	13.65		
40ft	37'12"	7.68		
50ft	47'6"	4.91		

PAR36 10W 3000K 120° CANDLEPOWER: 610.89		
Distance	Foot	Candles
2ft	6'8"	520.99
4ft	13'3"	130.25
6ft	19'11"	57.89
8ft	26'7"	32.56
10ft	33'3"	20.84
15ft	49'10"	9.26
20ft	66'5"	5.21
30ft	99'8"	2.32
40ft	132'11"	1.30
50ft	166'1"	0.83

PAR36 10W 5000K 15° CANDLEPOWER: 1026.63				
Distance	Distance Foot Candles			
2ft	5"	14298.17		
4ft	11"	3574.54		
6ft	1'4"	1588.69		
8ft	1'9"	893.64		
10ft	2'3"	571.93		
15ft	3'4"	254.19		
20ft	4'5"	142.98		
30ft	6'8"	63.55		
40ft	8'11"	35.75		
50ft	11'1"	22.88		

PAR36 10W 5000K 24° CANDLEPOWER: 1000.32			
Distance Foot Candles			
2ft	10"	12680.30	
4ft	1'7"	3170.08	
6ft	2'5"	1408.92	
8ft	3'3"	792.52	
10ft	4'1"	507.21	
15ft	6'1"	225.43	
20ft	8'1"	126.80	
30ft	12'1"	56.36	
40ft	16'2"	31.70	
50ft	20'2"	20.29	

PAR36 10W 5000K 38° CANDLEPOWER: 986.56		
Distance	Foot	Candles
2ft	1'3"	3562.76
4ft	2'7"	890.69
6ft	3'10"	395.86
8ft	5'1"	222.67
10ft	6'5"	142.51
15ft	9'7"	63.34
20ft	12'9"	35.63
30ft	19'2"	15.83
40ft	25'7"	8.91
50ft	31'12"	5.70

PAR36 10W 5000K 60° CANDLEPOWER: 970.93			
Distance Foot Candles			
2ft	1'11"	3120.45	
4ft	3'9"	780.11	
6ft	5'8"	346.72	
8ft	7'7"	195.03	
10ft	9'6"	124.82	
15ft	14'3"	55.47	
20ft	18'12"	31.20	
30ft	28'6"	13.87	
40ft	37'12"	7.80	
50ft	47'6"	4.99	

PAR36 10W 5000K 120° CANDLEPOWER: 635.92		
Distance	Foot	Candles
2ft	6'8"	542.30
4ft	13'3"	135.58
6ft	19'11"	60.26
8ft	26'7"	33.89
10ft	33'3"	21.69
15ft	49'10"	9.64
20ft	66'5"	5.42
30ft	99'8"	2.41
40ft	132'11"	1.36
50ft	166'1"	0.87

PAR 36 13W

PAR36 13W 2700K 15° CANDLEPOWER: 1150.56		
Distance	Foot	Candles
2ft	7"	18955.87
4ft	1'2"	4738.97
6ft	1'9"	2106.21
8ft	2'4"	1184.74
10ft	2'11"	758.23
15ft	4'5"	336.99
20ft	5'11"	189.56
30ft	8'10"	84.25
40ft	11'10"	47.39
50ft	14'19"	30.33

PAR36 13W 2700K 24° CANDLEPOWER: 1100.32		
Distance	Foot	Candles
2ft	11"	9477.93
4ft	1'11"	2369.48
6ft	2'10"	1053.10
8ft	3'10"	592.37
10ft	4'9"	379.12
15ft	7'2"	168.50
20ft	9'7"	94.78
30ft	14'4"	42.12
40ft	19'2"	23.69
50ft	23'11"	15.16

PAR36 13W 2700K 38° CANDLEPOWER: 1045.36		
Distance	Foot	Candles
2ft	1'2"	7723.14
4ft	2'3"	1930.79
6ft	3'5"	858.13
8ft	4'6"	482.70
10ft	5'8"	308.93
15ft	8'6"	137.30
20ft	11'4"	77.23
30ft	17'1"	34.33
40ft	22'9"	19.31
50ft	28'5"	12.36

PAR36 13W 2700K 60° CANDLEPOWER: 1034.96		
Distance	Foot	Candles
2ft	2'4"	3134.45
4ft	4'8"	783.61
6ft	6'1"	348.27
8ft	8'2"	195.90
10ft	10'2"	125.38
15ft	15'3"	55.72
20ft	20'4"	31.34
30ft	30'6"	13.93
40ft	40'8"	7.84
50ft	50'10"	5.02

PAR36 13W 2700K 120° CANDLEPOWER: 673.536		
Distance	Foot	Candles
2ft	6'8"	575.35
4ft	13'3"	143.84
6ft	19'11"	63.93
8ft	26'6"	35.96
10ft	33'2"	23.01
15ft	49'9"	10.23
20ft	66'3"	5.75
30ft	99'5"	2.56
40ft	132'7"	1.44
50ft	165'8"	0.92

PAR36 13W 3000K 15° CANDLEPOWER: 1168.32		
Distance	Foot	Candles
2ft	7"	19248.44
4ft	1'2"	4812.11
6ft	1'9"	2138.72
8ft	2'4"	1203.03
10ft	2'11"	769.94
15ft	4'5"	342.19
20ft	5'11"	192.48
30ft	8'10"	85.55
40ft	11'10"	48.12
50ft	14'19"	30.80

PAR36 13W 3000K 24° CANDLEPOWER: 1120.12		
Distance	Foot	Candles
2ft	11"	9648.44
4ft	1'11"	2412.11
6ft	2'10"	1072.05
8ft	3'10"	603.03
10ft	4'9"	385.94
15ft	7'2"	171.53
20ft	9'7"	96.48
30ft	14'4"	42.88
40ft	19'2"	24.12
50ft	23'11"	15.44

PAR36 13W 3000K 38° CANDLEPOWER: 1064.97		
Distance	Foot	Candles
2ft	1'2"	7868.03
4ft	2'3"	1967.01
6ft	3'5"	874.23
8ft	4'6"	491.75
10ft	5'8"	314.72
15ft	8'6"	139.88
20ft	11'4"	78.68
30ft	17'1"	34.97
40ft	22'9"	19.67
50ft	28'5"	12.59

PAR36 13W 3000K 60° CANDLEPOWER: 1045.5		
Distance	Foot	Candles
2ft	2'4"	3166.42
4ft	4'8"	791.60
6ft	6'1"	351.82
8ft	8'2"	197.90
10ft	10'2"	126.66
15ft	15'3"	56.29
20ft	20'4"	31.66
30ft	30'6"	14.07
40ft	40'8"	7.92
50ft	50'10"	5.07

PAR36 13W 3000K 120° CANDLEPOWER: 683.56		
Distance	Foot	Candles
2ft	6'8"	583.96
4ft	13'3"	145.99
6ft	19'11"	64.88
8ft	26'6"	36.50
10ft	33'2"	23.36
15ft	49'9"	10.38
20ft	66'3"	5.84
30ft	99'5"	2.60
40ft	132'7"	1.46
50ft	165'8"	0.93

PAR36 13W 5000K 15° CANDLEPOWER: 1180.48		
Distance	Foot	Candles
2ft	7"	19448.76
4ft	1'2"	4862.19
6ft	1'9"	2160.97
8ft	2'4"	1215.55
10ft	2'11"	777.95
15ft	4'5"	345.76
20ft	5'11"	194.49
30ft	8'10"	86.44
40ft	11'10"	48.62
50ft	14'19"	31.12

PAR36 13W 5000K 24° CANDLEPOWER: 1140.89		
Distance	Foot	Candles
2ft	11"	9827.45
4ft	1'11"	2456.86
6ft	2'10"	1091.94
8ft	3'10"	614.22
10ft	4'9"	393.10
15ft	7'2"	174.71
20ft	9'7"	98.27
30ft	14'4"	43.68
40ft	19'2"	24.57
50ft	23'11"	15.72

PAR36 13W 5000K 38° CANDLEPOWER: 1070.56		
Distance	Foot	Candles
2ft	1'2"	7909.37
4ft	2'3"	1977.34
6ft	3'5"	878.82
8ft	4'6"	494.34
10ft	5'8"	316.37
15ft	8'6"	140.61
20ft	11'4"	79.09
30ft	17'1"	35.15
40ft	22'9"	19.77
50ft	28'5"	12.65

PAR36 13W 5000K 60° CANDLEPOWER: 1080.63		
Distance	Foot	Candles
2ft	2'4"	3272.77
4ft	4'8"	818.19
6ft	6'1"	363.64
8ft	8'2"	204.55
10ft	10'2"	130.91
15ft	15'3"	58.18
20ft	20'4"	32.73
30ft	30'6"	14.55
40ft	40'8"	8.18
50ft	50'10"	5.24

PAR36 13W 5000K 120° CANDLEPOWER: 705.89		
Distance	Foot	Candles
2ft	6'8"	603.01
4ft	13'3"	150.75
6ft	19'11"	67.00
8ft	26'6"	37.69
10ft	33'2"	24.12
15ft	49'9"	10.72
20ft	66'3"	6.03
30ft	99'5"	2.68
40ft	132'7"	1.51
50ft	165'8"	0.96





The Decor Group